




Features

RM10C HYBRID RECORDER



- Short Case Depth and Light Weight
Dimension: 144W×144H×150D(mm)~
Weight: 1.5kg~
- IP-65: Dust-Proof, Water-Proof
- Highly Responsive and Multi-Functional
- Universal Input and Range
- RS-232C Provided as Standard
- Without Transducer
RM10C (pH) Sensor Input:
Glass or Metal Electrode (pH/ORP)
- UL, CSA, CE Approved

SPECIFICATIONS

TITLE	ITEM	PEN RECORDER	MULTIPOINT RECORDER	pH RECORDER
Input	Measuring Point	1, 2	6	1
	Input sampling	125ms	10s/6ch	200ms
	Type of input	Direct voltage: $\pm 10\text{mV}$, 0-20mV, 0-50mV, $\pm 200\text{mV}$, $\pm 1\text{V}$, $\pm 10\text{V}$, 0-5V		Glass electrode (pH or ORP)
		Direct current: 4-20mA (250 Ω shunt resistance required)		Temperature compensation:
		Thermocouple: K, T, J, E, B, S, R, C, N, PR40-20, PL II, L, Au-Fe, U		350 Ω , 500 Ω , 1k Ω , 6.8k Ω , 10k Ω
		RTD: Pt100, JPt100		
Analog retransmission				4-20mA DC isolated, 550 Ω max. (Option)
Performance	Accuracy	$\pm(0.2\%$ of rdg + 3digits) max. for Digital indicator		Linearity: $\pm 0.03\text{pH}(\pm 3\text{mV})$ Repeatability: $\pm 0.02\text{pH}(\pm 1\text{mV})$
	Noise reduction	NMRR: 60dB min. (50/60Hz $\pm 0.1\text{Hz}$) CMRR: 140dB min. (50/60Hz $\pm 0.1\text{Hz}$)		100dB min. (50/60Hz $\pm 0.1\text{Hz}$)
	Isolation resistance	0.5kV DC 20M Ω min. between the each terminal and grounding terminal		0.5kV DC 1000M Ω min. between R and G terminal and grounding terminal
	Dielectric strength	1.5kV AC for 1 minute between power terminal and grounding terminal		
		0.5kV AC for 1 minute between input terminal and grounding terminal		
	Vibration resistance	10 to 60Hz 1m/s ² max.		
	Shock resistance	2m/s ² max.		
Alarm	Nos.of relay outputs	3 outputs (Form A contacts: Built-in option)	6 outputs (Form A contacts: Built-in option)	2 Alarm outputs, 2 types(H,L) 1 Error output(Form A contacts: Built-in option)
	Alarm output contact capacity	250V AC 3A max. .(resistance load), 30V DC 3A max. .(resistance load)		
Communication	Interface	RS-232C (Standard), RS-485 (Option)		RS-232C (Standard)
Power supply	Rated power voltage	100-240VAC (50/60Hz)		
	Power consumption	30VA max.(100V AC)	25VA max.(100V AC)	20VA max.(100V AC)
Structure	Mounting/Housing	Panel mounting / Front panel: Dust-proof, Water-proof (IP-65)		
	Dimension	144(W)x144(H)x150(D)mm		144(W)x144(H)x174(D)mm
	Weight	1.8kg max.	1.5kg max.	2.0kg max.
Operation condition	Allowable conditions	Temperature: 0-50°C, Humidity: 20-80%RH		
Recording /Printing Performance	Recording	Disposable felt pen	Wire dot 6 color ribbon	Disposable felt pen
	Printing	Wire dot 1 color ribbon		Wire dot 1 color ribbon
	95% step response time	1.0s max.		1.0s max.
	Dot print interval		10.0s/6ch max.	
	Chart paper	Length: 16m, Width: 114mm, Width folded: 40mm		
	Chart speed	User-selective from 41 speeds	User-selective from 34 speeds	
		in range: 5-12000mm/hr.	in range: 0-1500mm/hr.	in range: 5-12000mm/hr.
	Recording/Printing Color	Red, Green	Purple, Red, Green, Blue, Brown, Black	Red
Safety Standard and EMI Standard	Electrical safety	IEC1010-1, UL3101-1 installation category II and pollution degree 2. UL3101-1		
	Emissions	EN55011 Group1 Class A		
	Immunity	EN50082-2		